

# WWR2900

PEN BARCODE SCANNER



*Productivity Solutions for Small Businesses*

The WWR2900 pen barcode scanner is the perfect tool for repetitive data entry. Use the WWR2900 to scan barcodes on invoices, membershipcards, and other barcoded material.

The barcode data is instantly transferred to your open document, spreadsheet, or database, helping your business save time and eliminate data entry errors. The WWR2900 connects easily through your PC's USB port, and offers a compact, pen-style design that is ideal for desktop use.

## ■ WASP WWR2900 FEATURES

- ▶ Scans barcode data on contact
- ▶ Durable, ABS plastic construction provides reliability
- ▶ Can withstand multiple 6' drops to concrete
- ▶ Supports pre-amble and post-amble characters, including function keys
- ▶ Reads linear (1D) barcodes, including Code 39, Code 128 and UPC
- ▶ Compatible with optional stand for easy access and storage
- ▶ Includes 6' coiled USB cable

## ■ WASP WWR2900 COMMON USES

- ▶ Office
- ▶ Library
- ▶ Medical
- ▶ Marketing

## ■ BENEFITS

- ▶ Easily scan barcodes on invoices, documents, and membership cards by swiping the WWR2900 across the barcode
- ▶ Rapidly add data to your open application, eliminating data-entry errors and improving efficiency
- ▶ Ensure user comfort with the WWR2900's ergonomic, pen-style design
- ▶ Compact, space-saving design integrates easily into desktop workspaces
- ▶ Quickly install the WWR2900 through your PC's USB port without additional software or drivers

# WWR2900

PEN BARCODE SCANNER



*Productivity Solutions for Small Businesses*

## ■ SPECIFICATIONS

<b>OPTICAL FEATURES</b>	Depth of field: 1 mm Resolution: 0.127 mm (5 mil) Rate: 100 mm - 600 mm / Sec Tilt angle: 45 - 90 degree
<b>ELECTRICAL CHARACTERISTICS</b>	Light source: 650 nm LED Sensor: Photo Diode Supply voltage: 5 VDC $\pm$ 10% Surge power: <500 mA Working current (WWR2905): 60 mA $\pm$ 10 mA
<b>MECHANICAL CHARACTERISTICS</b>	Dimensions: 5.9" W x 1.17" H x 0.87" D (150 mm W x 29.6 mm H x 22 mm D) Net weight: 76 g Cable: 6 ft. coiled
<b>ENVIRONMENT CHARACTERISTICS</b>	Operating temperature: 32°F to 122°F (0°C to 50°C) Storage temperature: -4°F to 140°F (-20°C to 60°C) Relative humidity: 0% RH to 95% RH (non-condensing) Mechanical shock: 6.0 ft. (1.85) drop onto concrete
<b>SAFETY CERTIFICATION</b>	FCC class A and CE approval
<b>1D (LINEAR) SYMBOLOGIES READ</b>	Codabar, Code 3 of 9 (Code 39), Code 3 of 9 Full ASCII, Code 11, Code 32, Code 93, Code 128 (including UCC/EAN 128), EAN/JAN-8 (plus supplements), EAN/JAN-13 (plus supplements), Industrial 2 of 5 (25), Interleaved 2 of 5, ISBN, Matrix 25, MSI Plessey, UPC-A (plus supplements), UPC-E (plus supplements), China Post Code, RSS14, Telepen
<b>PART NUMBERS</b>	WWR2900 Pen Barcode Scanner with USB cable: 633808142421 WWR2900 Pen Barcode Scanner Stand: 633808142438 WaspProtect 2-Year Extended Warranty for WWR2900 Barcode Scanner: 633808600006 WaspProtect 1-Year Renewal for WWR2900 Barcode Scanner: 633808600327